

EARTHMAX SR 423 - Teknik Özellikler



Description

EARTHMAX SR 423, taş ocağı, taşıma ve ağır kütük operasyonları dahil olmak üzere çeşitli uygulamalara uygun Tamamen Çelik bir radyal lastiktir. Yönsüz sırt deseni her türlü arazide mükemmel çekiş ve sabitleme sağlar. Lastik, ağır yüklerle çalışmak için idealdir. Güçlü Tamamen Çelik gövde, mükemmel aşınma ömrü ve takımalara ve delinmelere karşı direnç sunar. Güçlendirilmiş damağı ve omuz tasarımı, ağır hizmet koşullarında bile uzun lastik kullanım ömrüne katkıda bulunur.

UM

US Standard

Construction

 RADIAL

Machinery

Yoldışı: Yol ve yol dışı kamyon

| | |
|-----------|-----------------------------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 325/95 R 24 (12.00 R 24) |
| LI/SS | 160/156 K |

Dimensions US Standard

| | |
|-------------------------|----------|
| Usa code | 94063727 |
| Overall Width (inch) | 12.5 |
| Overall Diameter (inch) | 48.9 |
| Rim Rec | 8.50 |

Load capacity (lbs)

| mph / psi | 125 |
|----------------|------|
| 68 Load Single | 9920 |
| 68 Load Dual | 8820 |

Printed on 19.05.2024 13:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..