

EARTHMAX SR 484 - Teknik Özellikler



Description

EARTHMAX SR 484, özellikle açık maden işletmesi uygulamalarındaki taşıma operasyonlarına yönelik olan sabit kaya kamyonları için tasarlanmış, Tamamen Çelikten yapılmış bir radyal lastiktir. Geliştirilmiş çekiş ve kendiliğinden temizlenme özellikleri ile birlikte, kayalık ve sert koşullarda mükemmel koruma sağlayan özel sırt hamuru ile benzersiz bir E-3 sırt tasarımına sahiptir. Çok katmanlı çelik kuşaklara sahip Tamamen Çelik yapısı, çalışma süresini artırmak ve daha yüksek üretkenlik için şok, yorgunluk ve kaya delmelerine karşı üstün koruma sağlar. EARTHMAX SR 484, mükemmel manevra kabiliyeti ve sabitleme için zemin temasını en üst düzeye çıkaran kare omuz tasarımına sahiptir. Bu BTK lastiği özellikle daha yüksek hızlar ve uzun mesafeler için tasarlanmıştır.

UM

International Standard

Construction

 RADIAL

Machinery

Yoldışı: Sabit kaya kamyonu

Version	STANDARD COMPOUND
Type	TL
Tyre Size	27.00 R 49
LI/SS	223 B

Dimensions International Standard

TKPH	610
Overall Width (mm)	735
Overall Diameter (mm)	2647
Static Loaded Radius (mm)	1193
Rolling Circumference (mm)	8055
Rim Rec	19.50/4.0
Rim Alt	--
Star Rating	**
TRA Code	E3

Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	20600	21800	22400	23000	23600	25000	25750	26500	27250

Printed on 5/20/2024 12:02 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..