

## EARTHMAX SR 49 M - Teknik Özellikler



### Description

EARTHMAX SR 49 M, özellikle yeraltı madenciliğinde zorlu kayalık koşullarında çalışan dozerler, yükleyiciler, düşük profilli damperli kamyonlar (LPDT) ve yük taşıma damperleri (LHD) için tasarlanmış, özel yönsüz desene sahip Tamamen Çelik bir radyal lastiktir. EARTHMAX SR 49 M, olağanüstü çekiş ve sabitleme gerektiren zorlu işlemler için idealdir. L-4 derin sırt ve özel olarak formüle edilmiş UMS (yeraltı madeni hizmeti) hamuru, kaya kesiklerine ve delinmelere karşı mükemmel dirence ek olarak daha uzun bir lastik aşınma ömrü sağlar.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Yoldışı: Dozer • Yük taşıma damperli (LHD) • Yükleyici • Düşük profilli damperli kamyon

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	29.5 R 29
LI/SS	223 A2

## Dimensions International Standard

Overall Width (mm)	786
Overall Diameter (mm)	2006
Static Loaded Radius (mm)	906
Rolling Circumference (mm)	6320
Rim Rec	25.00/3.5
Rim Alt	24.00/3.5,26.00/3.5
Star Rating	***
TRA Code	L4

## Load capacity (Kg)

km/h / bar	6.75	7.00	7.25	7.50	7.75	8.00
10	24300	25000	25750	26200	26700	27250

Printed on 5/19/2024 5:08 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..