

EARTHMAX SR 49 M - Veri Sayfasını İndir



Description

EARTHMAX SR 49 M, özellikle yeraltı madenciliğinde zorlu kayalık koşullarında çalışan dozerler, yükleyiciler, düşük profilli damperli kamyonlar (LPDT) ve yük taşıma damperleri (LHD) için tasarlanmış, özel yönsüz desene sahip Tamamen Çelik bir radyal lastiktir. EARTHMAX SR 49 M, olağanüstü çekiş ve sabitleme gerektiren zorlu işlemler için idealdir. L-4 derin sırt ve özel olarak formüle edilmiş UMS (yeraltı madeni hizmeti) hamuru, kaya kesiklerine ve delinmelere karşı mükemmel dirence ek olarak daha uzun bir lastik aşınma ömrü sağlar.

UM

International Standard

Construction

 RADIAL

Machinery

Yoldışı: Dozer • Yük taşıma damperli (LHD) • Yükleyici • Düşük profilli damperli kamyon

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
26.5 R 25	CUT RESISTANT COMPOUND	L4	**	209 A2	22.00/3.0		708	1782	801	5297	TL	
26.5 R 25	CUT RESISTANT COMPOUND	E4/L4	**/*	193 B/202 A2	22.00/3.0		708	1782	801	5297	TL	165
26.5 R 25	CUT RESISTANT COMPOUND	L4	*	202 A2	22.00/3.0		708	1782	801	5297	TL	
26.5 R 25	CUT RESISTANT COMPOUND	E4/L4	****/***		22.00/3.0		708	1782	801	5297	TL	
26.5 R 25	CUT RESISTANT COMPOUND (UMS)	E4	****		22.00/3.0		708	1782	801	5297	TL	
29.5 R 25	CUT RESISTANT COMPOUND	L4	*	208 A2	25.00/3.5		780	1905	844	5600	TL	
29.5 R 25	CUT RESISTANT COMPOUND	L4	**	216 A2	25.00/3.5		780	1905	844	5600	TL	
29.5 R 25	CUT RESISTANT COMPOUND	E4/L4	**/*	200 B/208 A2	25.00/3.5		780	1905	844	5600	TL	220
29.5 R 25	CUT RESISTANT COMPOUND	E4/L4	****/***		25.00/3.5		780	1905	844	5600	TL	
29.5 R 25	CUT RESISTANT COMPOUND (UMS)	E4	****		25.00/3.5		780	1905	844	5600	TL	
29.5 R 29	CUT RESISTANT COMPOUND	L4	***	223 A2	25.00/3.5	24.00/3.5,26.00/3.5	786	2006	906	6320	TL	
29.5 R 29	CUT RESISTANT COMPOUND (UMS)	E4	****		25.00/3.5	24.00/3.5, 26.00/3.5	786	2006	906	6320	TL	

Printed on 5/19/2024 4:40 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..