

## MULTIMAX MP 522 - Teknik Özellikler



### Description

MULTIMAX MP 522, tarımsal sanayi uygulamaları için geliştirilmiş çok amaçlı BKT lastiğidir. Teleskopik yükleyiciler ve küçük yükleyiciler gibi araçlarla gerçekleştirilen tüm kaldırma ve yükleme işlemleri için uygundur. Olağanüstü delinme direncinin yanı sıra sabitleme ve çekiş güçlü taraflarıdır. Özel hamuru sayesinde MULTIMAX MP 522, inanılmaz bir kesilme ve kopma direncine sahiptir.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Zirai: Küçük yükleyici • Teleskopik yükleyici  
Endüstriyel: Küçük yükleyici • Teleskopik yükleyici

Version	STANDARD
Type	TL
Tyre Size	340/80 R 18 IND (12.5/80 R 18)
LI/SS	143 A8/B

## Dimensions International Standard

Section Width (mm)	343
Overall Diameter (mm)	1006
Static Loaded Radius (mm)	458
Rolling Circumference (mm)	3023
SRI (mm)	475
Rim Rec	11 ; 11 SDC ; W 11
Rim Alt	W 10 ; 12 ; 12 SDC
ECE	E4-106R-002654

## Load capacity (Kg)

km/h / bar	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	1310	1555	1775	2020	2265	2430	2725	-	-
40	1310	1555	1775	2020	2265	2430	2725	-	-
30	1405	1665	1900	2165	2425	2600	2920	-	-
25	1455	1725	1970	2240	2515	2695	3025	-	-
10 Cyc.	1600	1965	2315	2660	3030	3295	3725	3930	4090
Static	2450	3010	3545	4080	4640	5050	5710	6020	6270

Printed on 5/19/2024 5:16 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..