

MULTIMAX MP 522 - Teknik Özellikler



Description

MULTIMAX MP 522, tarımsal sanayi uygulamaları için geliştirilmiş çok amaçlı BKT lastiğidir. Teleskopik yükleyiciler ve küçük yükleyiciler gibi araçlarla gerçekleştirilen tüm kaldırma ve yükleme işlemleri için uygundur. Olağanüstü delinme direncinin yanı sıra sabitleme ve çekiş güçlü taraflardır. Özel hamuru sayesinde MULTIMAX MP 522, inanılmaz bir kesilme ve kopma direncine sahiptir.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: Küçük yükleyici • Teleskopik yükleyici
Endüstriyel: Küçük yükleyici • Teleskopik yükleyici

Version	STANDARD
Type	TL
Tyre Size	340/80 R 20 IND
LI/SS	144 A8/B

Dimensions US Standard

Usa code	94052875
Section Width (inch)	13.5
Overall Diameter (inch)	41.4
Static Loaded Radius (inch)	18.9
Rolling Circumference (inch)	126.5
Rim Rec	11
Rim Alt	W10 ; 11 SDC ; W11 ; 12 ; 12 SDC
ECE	E11-106R-002969

Load capacity (lbs)

mph / psi	23	29	35	41	46	51	58	61	64
30	2970	3530	4010	4570	5130	5500	6170	-	-
25	2970	3530	4010	4570	5130	5500	6170	-	-
20	3170	3770	4300	4890	5490	5890	6610	-	-
15	3300	3910	4460	5080	5700	6110	6860	-	-
5 Cvc.	3620	4450	5240	6020	6860	7460	8430	8900	9260
Static	5540	6820	8020	9240	10520	11430	12930	13630	14200

Printed on 5/19/2024 1:32 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..