

RT 747 AGRO INDUSTRIAL - Teknik Özellikler



Description

RT 747 AGRO INDUSTRIAL, küçük yükleyiciler ve teleskopik yükleyicilere uygun tarımsal sanayi amaçlı bir radyal lastiktir. Ekstra geniş dişleri, kaldırma işlemlerinde mükemmel çekiş ve müthiş sabitleme sağlar. Lastiğin ağır yükleri taşıyabilmesini sağlayan özel bir kesilme ve kopma direncine sahip hamur ile tasarlanmıştır. RT 747 AGRO INDUSTRIAL, olağanüstü çok yönlülük gerektiren tüm genel tarım operasyonları için doğru cevaptır.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: Küçük yükleyici • Teleskopik yükleyici
Endüstriyel: Küçük yükleyici • Teleskopik yükleyici

| | |
|-----------|----------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 11L R 16 |
| LI/SS | 122 A8/B |

Dimensions US Standard

| | |
|-------------------------|-----------------|
| Usa code | 94062737 |
| Section Width (inch) | 11.4 |
| Overall Diameter (inch) | 33.5 |
| Rim Rec | W 8 |
| Rim Alt | W 10 L |
| ECE | E11-106R-005769 |

Load capacity (lbs)

| mph / psi | 17 | 23 | 29 | 32 | 35 | 38 |
|-----------|------|------|------|------|------|------|
| 5 | 2790 | 3370 | 3950 | 4230 | 4530 | 4850 |
| 15 | 2070 | 2570 | 3050 | 3310 | 3550 | --- |
| 25 | 1940 | 2390 | 2850 | 3080 | 3310 | --- |

Printed on 5/19/2024 10:30 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..