

TR 387 IND - Teknik Özellikler



Description

TR 387 IND, endüstriyel römorklar ve kompaktörler için uygun endüstriyel bir lastiktir. Yüksek yük kapasitesi sağlar, ayrıca kesik ve kopma direnci, ağır hizmetler ve dayanıklılık bakımından özel kullanıcı gereksinimlerini karşılamak için farklı modellerde mevcuttur. "Çift damak telli" modeli özellikle endüstriyel traktörler ve römork kullanılarak yapılan taşımacılık operasyonları için uygundur.

UM

US Standard

Construction

BIAS

Machinery

Endüstriyel: Kompaktör • Traktör • Römork

| | |
|-----------|----------------------------|
| Version | DUAL BEAD HD |
| Type | TL |
| Tyre Size | 620/75 - 30 (23.1 - 30) |
| LI/SS | 160 A8 |

Dimensions US Standard

| | |
|-------------------------|-------------------|
| Usa code | 94065325 |
| Ply Rating | 18 |
| Section Width (inch) | 23.8 |
| Overall Diameter (inch) | 65.9 |
| Rim Rec | DW 20 A ; DW 20 B |
| TRA Code | R3 |

Load capacity (lbs)

| mph / psi | 38 |
|-----------|-------|
| 25 | 11000 |

Printed on 5/19/2024 10:49 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..