

XL GRIP (L3) - Teknik Özellikler



Description

XL GRIP (E-3/L-3) ağır yük gerektiren yükleme uygulamalarında kesilme ve delinmeleri en aza indirmek üzere tasarlanmış, yükleyicilere yönelik geniş tabanlı, çapraz kuşaklı bir lastiktir. Uzun bir lastik ömrü ile birlikte, sıra dışı çekiş gücü sağlar.

UM

US Standard

Construction

BIAS

Machinery

Endüstriyel: Yükleyici
Yoldışı: Dozer • Yükleyici

Version

STANDARD

Type

TL

Tyre Size

20.5 - 25

Dimensions US Standard

| | |
|------------------------------|-----------|
| Usa code | 94015856 |
| Ply Rating | 20 |
| Overall Width (inch) | 20.9 |
| Overall Diameter (inch) | 58.5 |
| Static Loaded Radius (inch) | 26.9 |
| Rolling Circumference (inch) | 173 |
| Rim Rec | 17.00/2.0 |
| TRA Code | E3/L3 |

Load capacity (lbs)

| mph / psi | 47 | 65 |
|-----------|-------|-------|
| 30 | 13200 | - |
| 5 | - | 20900 |

Printed on 5/19/2024 9:50 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..