

# **AGRIMAX V-FLECTO - Technical Specifications**



## Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for highpower tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the exclusive VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

## UM

**US Standard** 

#### Construction

🕈 RADIAL

## Machinery

Agriculture: High-Power Tractor

Version	STANDARD
Туре	TL
Tyre Size	VF 600/60 R 34
LI/SS	160 D

# **Dimensions US Standard**

Usa code	94074495
Section Width (inch)	23.4
Overall Diameter (inch)	62.4
Static Loaded Radius (inch)	27.2
Rolling Circumference (inch)	185.4
Rim Rec	DW 20 B
Rim Alt	DW 18 L ; DW 21 B
Narrow Rim option	DW 18 L
ECE	E11-106R-008773
TRA Code	R1W

# Load capacity (lbs)

mph / psi	9	12	15	17	20	23
45	4960	5780	6580	7400	8210	9030
from 40 to 25	5460	6350	7240	8130	9030	9920
20	5560	6470	7390	8290	9200	10120
12	5670	6600	7530	8450	9380	10320
5	6000	6980	7960	8940	9920	10910
*Upto 5 Cyc with front loader	7640	8880	10130	11390	12630	13890
5 HT	5560	6470	7390	8290	9200	10120

#### \* \*For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

#### Printed on 5/19/2024 6:43 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..