

AGRIMAXFACTOR - Technical Specifications



Description

AGRIMAXFACTOR is BKT's brand-new 70 series for tractors that is perfect for both haulage and soil tillage operations. The improved tread design with further increased lug length and changed lug orientation stands for better roadability. The reduced lug angle ensures less rolling resistance, whilst the by 5 % increased contact area on the land significantly reduced the noise perception in the cabin – both features stand for more comfort. In addition, the strong polyester casing provides extraordinary lateral stability and a faster steering response even for high-speed operations or heavy-duty service. The tire's braking results on wet surface are excellent.

In a nutshell, AGRIMAXFACTOR's overall advantages are great handling in combination with under many aspects extraordinary driving comfort in addition to excellent durability – all particular requirements by increasingly heavier machinery including the higher weight of e-vehicles' battery packages. The exclusive sidewall shows the perfectly aligned "E-READY" logo that highlights BKT's commitment to electric mobility.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	710/70 R 38
LI/SS	171 D/174 A8

Dimensions International Standard

Section Width (mm)	716
Overall Diameter (mm)	1959
Static Loaded Radius (mm)	866
Rolling Circumference (mm)	5800
SRI (mm)	925
Rim Rec	DW 23 B
Rim Alt	DW 25 B
ECE	E11-106R-007637
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	2895	3325	3815	4305	4800	5290	5785	6150
50	3040	3490	4010	4525	5040	5560	6075	6460
40	3150	3620	4155	4690	5230	5765	6300	6700
30	3330	3825	4390	4955	5520	6085	6655	7075
10 LT	3880	4455	5115	5775	6435	7095	7755	8245
10 HT	3330	3825	4390	4955	5520	6085	6655	7075

Printed on 5/19/2024 1:06 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..