

# MULTIMAX MP 522 - Technical Specifications



## Description

MULTIMAX MP 522 is the BKT multi-purpose tire developed for agro-industrial applications. It is suitable for all lifting and loading operations on vehicles such as telehandlers and compact loaders. Stability and traction are its strengths as well as outstanding puncture resistance. Thanks to its special compound, MULTIMAX MP 522 has an incredible cut and chip resistance.

## UM

International Standard

## Construction

 RADIAL

## Machinery

Agriculture: Compact Loader • Telehandler  
Industrial: Compact Loader • Telehandler

Version	STANDARD
Type	TL
Tyre Size	540/70 R 24 IND
LI/SS	168 A8/B

## Dimensions International Standard

Section Width (mm)	530
Overall Diameter (mm)	1366
Static Loaded Radius (mm)	611
Rolling Circumference (mm)	4133
SRI (mm)	650
Rim Rec	DW 16 L
Rim Alt	DW 18 L
ECE	E11-106R-002967

## Load capacity (Kg)

km/h / bar	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	2690	3195	3640	4145	4650	4985	5600	-	-
40	2690	3195	3640	4145	4650	4985	5600	-	-
30	2880	3420	3900	4440	4980	5340	5995	-	-
25	2990	3550	4045	4605	5165	5540	6220	-	-
10 Cyc.	3280	4035	4750	5460	6220	6765	7645	8065	8400
Static	5025	6185	7280	8375	9535	10370	11725	12365	12880

Printed on 5/19/2024 11:53 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..