

## AGRIMAX ELOS - Technical Specifications



### Description

AGRIMAX ELOS has been designed to enhance top traction performance even under particularly awkward operating conditions on wet terrains such as paddy fields or marshland. The tread design has been especially developed to ensure optimum self-cleaning properties, which are essential for operations on muddy land and during transfers. To optimize the farmers' productivity reducing machine downtime, sidewall protectors have been integrated into the design of the AGRIMAX ELOS tire to ensure maximum protection against possible damages at any time.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Tractor

|           |                            |
|-----------|----------------------------|
| Version   | STANDARD                   |
| Type      | TL                         |
| Tyre Size | 340/85 R 38<br>(13.6 R 38) |
| LI/SS     | 133 A8/B                   |

## Dimensions US Standard

|                              |                |
|------------------------------|----------------|
| Usa code                     | 94040452       |
| Section Width (inch)         | 13.9           |
| Overall Diameter (inch)      | 63.1           |
| Static Loaded Radius (inch)  | 28.9           |
| Rolling Circumference (inch) | 188            |
| Rim Rec                      | W 12           |
| Rim Alt                      | W 11           |
| ECE                          | E4-106R-001477 |
| TRA Code                     | R2             |

## Load capacity (lbs)

| mph / psi | 9    | 12   | 15   | 17   | 20   | 23   |
|-----------|------|------|------|------|------|------|
| 30        | 2500 | 2910 | 3320 | 3730 | 4130 | 4540 |
| 25        | 2500 | 2910 | 3320 | 3730 | 4130 | 4540 |
| 20        | 2680 | 3120 | 3550 | 3990 | 4430 | 4860 |
| 5 LT      | 3360 | 3900 | 4450 | 5000 | 5560 | 6100 |
| 5 HT      | 2680 | 3120 | 3550 | 3990 | 4430 | 4860 |

Printed on 5/19/2024 2:15 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..