

AGRIMAX ELOS - Technical Specifications



Description

AGRIMAX ELOS has been designed to enhance top traction performance even under particularly awkward operating conditions on wet terrains such as paddy fields or marshland. The tread design has been especially developed to ensure optimum self-cleaning properties, which are essential for operations on muddy land and during transfers. To optimize the farmers' productivity reducing machine downtime, sidewall protectors have been integrated into the design of the AGRIMAX ELOS tire to ensure maximum protection against possible damages at any time.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	520/85 R 42 (20.8 R 42)
LI/SS	157 A8/B

Dimensions International Standard

Section Width (mm)	516
Overall Diameter (mm)	1988
Static Loaded Radius (mm)	904
Rolling Circumference (mm)	5865
SRI (mm)	925
Rim Rec	DW 16 L
Rim Alt	DD 18 L ; DW 18 L
ECE	E4-106R-000793
TRA Code	R2

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	2270	2640	3015	3385	3755	4125
40	2270	2640	3015	3385	3755	4125
30	2430	2830	3225	3625	4020	4415
10 LT	3045	3540	4040	4535	5035	5530
10 HT	2430	2830	3225	3625	4020	4415

Printed on 5/19/2024 11:15 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..