

AGRIMAX ELOS - Technical Specifications



Description

AGRIMAX ELOS has been designed to enhance top traction performance even under particularly awkward operating conditions on wet terrains such as paddy fields or marshland. The tread design has been especially developed to ensure optimum self-cleaning properties, which are essential for operations on muddy land and during transfers. To optimize the farmers' productivity reducing machine downtime, sidewall protectors have been integrated into the design of the AGRIMAX ELOS tire to ensure maximum protection against possible damages at any time.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	710/70 R 38
LI/SS	178 A8/B

Dimensions US Standard

Usa code	94058617
Section Width (inch)	28.2
Overall Diameter (inch)	79.5
Static Loaded Radius (inch)	36
Rolling Circumference (inch)	240.3
Rim Rec	DW 23 B
Rim Alt	DW 25 B
ECE	E11-106R-004896
TRA Code	R2

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35	41	46	52
30	6120	7110	8100	9260	10250	11240	12400	13060	14380	15540	16530
25	6120	7110	8100	9260	10250	11240	12400	13060	14380	15540	16530
20	6550	7620	8670	9910	10980	12040	13270	13980	15400	16630	17690
5 LT	8200	9530	10860	12410	13750	15070	16620	17500	19280	20830	22160
5 HT	6550	7620	8670	9910	10980	12040	13270	13980	15400	16630	17690

Printed on 5/19/2024 11:46 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..