

## AGRIMAX ELOS - Data Sheet



### Description

AGRIMAX ELOS has been designed to enhance top traction performance even under particularly awkward operating conditions on wet terrains such as paddy fields or marshland. The tread design has been especially developed to ensure optimum self-cleaning properties, which are essential for operations on muddy land and during transfers. To optimize the farmers' productivity reducing machine downtime, sidewall protectors have been integrated into the design of the AGRIMAX ELOS tire to ensure maximum protection against possible damages at any time.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Tractor

SIZE	Version	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
<b>420/85 R 28</b> (16.9 R 28)	STANDARD	R2	139 A8/B	W 15 L	W 13 ; W 14 L	438	1467	665	4349	700	TL	E4-106R-000768
<b>480/70 R 34</b>	STANDARD	R2	155 A8/155 B	W 15 L	W 16 L ; W 14 L	500	1605	733	4868	750	TL	E11-106R-007532
<b>340/85 R 38</b> (13.6 R 38)	STANDARD	R2	133 A8/B	W 12	W 11	353	1602	735	4774	775	TL	E4-106R-001477
<b>380/85 R 38</b> (14.9 R 38)	STANDARD	R2	139 A8/B	W 12	W 11 ; W 13	380	1662	772	4994	775	TL	E4-106R-000779
<b>420/85 R 38</b> (16.9 R 38)	STANDARD	R2	144 A8/B	W 15 L	W 13 ; W 14 L	438	1735	785	5135	825	TL	E4-106R-000780
<b>480/80 R 38</b> (18.4 R 38)	STANDARD	R2	149 A8/B	W 16 L	W 15 L ; DW 16 L	489	1803	821	5356	825	TL	E11-106R-002991
<b>710/70 R 38</b>	STANDARD	R2	178 A8/B	DW 23 B	DW 25 B	716	2019	915	6103	925	TL	E11-106R-004896
<b>480/80 R 42</b> (18.4 R 42)	STANDARD	R2	151 A8/B	DW 16 L	DD 16 L ; W 16 L	489	1890	857	5629	875	TL	E4-106R-001481
<b>520/85 R 42</b> (20.8 R 42)	STANDARD	R2	157 A8/B	DW 16 L	DD 18 L ; DW 18 L	516	1988	904	5865	925	TL	E4-106R-000793
<b>520/85 R 42</b> (20.8 R 42)	STANDARD	R2	167A8/B	DW 16 L	DD 18 L ; DW 18 L	516	1988	920	6095	925	TL	E11-106R-0010146
<b>520/85 R 46</b>	STANDARD	R2	169 A8/169 B	DW 16 L	DW 15 L ; DW 18 L ; W 15 L ; W 16 L ; W18 L ; DD 16 L ; DD 18 L	530	2075	957	6293	975	TL	E11-106R-007935

Printed on 5/19/2024 8:10 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..