

## AGRIMAX FORTIS - Technical Specifications



### Description

AGRIMAX FORTIS is your reliable partner for all preparation, soil tillage and haulage operations. Designed to equip the latest, most modern and most powerful tractors, AGRIMAX FORTIS allows you to carry very high loads reaching up to 65 km/h (40 MPH). It ensures outstanding traction along with top handling and best comfort for a perfect driving experience. The tire has been designed with a reinforced nylon casing for enhanced productivity in the fields preserving the soil thanks to reduced compaction.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Sprayer

Version	SPECIAL
Type	TL
Tyre Size	710/75 R 42
LI/SS	175 D/172 E

## Dimensions International Standard

Section Width (mm)	716
Overall Diameter (mm)	2133
Static Loaded Radius (mm)	970
Rolling Circumference (mm)	6406
SRI (mm)	1000
Rim Rec	DW 23 B
Rim Alt	DW 25 B
ECE	E4-106R-001835
TRA Code	R1W

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	3025	3530	3970	4410	4855	5230	5800	6300
65	3315	3865	4350	4830	5315	5730	6350	6900
50	3480	4060	4565	5075	5580	6015	6670	7245
40	3630	4235	4765	5295	5825	6275	6960	7560
30	3810	4445	5000	5555	6110	6590	7305	7935
10 LT	4440	5180	5830	6475	7125	7680	8510	9250
10 HT	3810	4445	5000	5555	6110	6590	7305	7935

Printed on 5/19/2024 5:29 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..