

AGRIMAX FORTIS - Technical Specifications



Description

AGRIMAX FORTIS is your reliable partner for all preparation, soil tillage and haulage operations. Designed to equip the latest, most modern and most powerful tractors, AGRIMAX FORTIS allows you to carry very high loads reaching up to 65 km/h (40 MPH). It ensures outstanding traction along with top handling and best comfort for a perfect driving experience. The tire has been designed with a reinforced nylon casing for enhanced productivity in the fields preserving the soil thanks to reduced compaction.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer

Version	STANDARD
Type	TL
Tyre Size	800/70 R 38
LI/SS	178 D/181 A8

Dimensions US Standard

Usa code	94032969
Section Width (inch)	31.4
Overall Diameter (inch)	82.1
Static Loaded Radius (inch)	35.9
Rolling Circumference (inch)	244.2
Rim Rec	DW 25 B
Rim Alt	DW 27 B
ECE	E4-106R-001424
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
40	7940	9260	10420	11570	12730	13720	15210	16500
30	8330	9720	10950	12160	13370	14420	15970	17360
25	8730	10180	11460	12730	14010	15100	16730	18190
20	9130	10650	11980	13320	14650	15780	17490	19010
5 LT	10640	12410	13970	15510	17060	18400	20390	22160
5 HT	9130	10650	11980	13320	14650	15780	17490	19010

Printed on 5/19/2024 4:50 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..