



AGRIMAX TERIS - Data Sheet



Description

Today's high-power harvesters require tires that are able to support heavy equipment and loads without damaging the crops. BKT is committed to provide you with radial tires at the cutting edge to increase your yield. AGRIMAX TERIS is the right partner for all your combined operations. Excellent traction properties and high load capacity are its essential features providing best performance in all harvesting operations. The special sidewall protection and a reinforced shoulder increase resistance - thus extending the product life-cycle - also in harsh conditions and if there are stubbles in the fields.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Cotton Picker • Harvester

SIZE	Version	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
620/75 R 26 CHO	STANDARD	166 A8/B	DW 20 B		625	1590	730	4851	750	TL	E4-106R-001419
750/65 R 26 CHO (28L R 26)	STANDARD	166 A8/B	DW 25 B	DW 23 B	764	1636	713	4908	750	TL	E4-106R-000810
750/65 R 26 CHO (28L R 26)	STANDARD	171 A8/B	DW 25 B	DW 23 B	764	1636	713	4908	750	TL	E4-106R-001496
710/55 R 28 CHO	STANDARD	164 A8/B	DW 23 B		716	1493	663	4442	700	TL	E11-106R-005940
620/75 R 30 CHO	STANDARD	168 A8/B	DW 20 B		625	1692	779	5169	800	TL	E4-106R-001420
1050/50 R 32 CHO	STANDARD	184 A8/181 B	36.0 VA		1059	1893	840	5685	875	TL	E4-106R-000813
650/75 R 32 CHO	STANDARD	172 A8/B	DW 21 B	DW 20 B ; DW 23 B	670	1795	816	5378	850	TL	E4-106R-001425
800/65 R 32 CHO (30.5L R 32)	STANDARD	178 A8/175 B	DW 27 B	DW 25 B ; DH 27 B	818	1853	838	5551	875	TL	E4-106R-001430
900/60 R 32 CHO	STANDARD	185 A8/182 B	DW 27 B	DW 28 B ; DW 30 B	875	1910	875	5775	900	TL	E4-106R-001433
900/60 R 32 CHO	STANDARD	181 A8/178 B	DW 27 B	DW 28 B ; DW 30 B	886	1910	854	5700	900	TL	E4-106R-001431
IF 710/75 R 32 CFO	STANDARD	183 A8/B	DW 25 B	DW 23 B	716	1879	851	5653	875	TL	E11-106R-005025
IF 580/80 R 34 CFO	STANDARD	177 D	DW 20 B ; DW 20 A	DW 21 A ; DW 21 B	586	1792	810	5422	850	TL	E4-106R-001833
IF 710/75 R 34 CFO	STANDARD	184 A8/B	DW 25 B		716	1930	870	5852	900	TL	E11-106R-004899
520/85 R 42	STANDARD	168 D	DW 16 L	W15L ; DW15L ; DD16L ; W16L ; DD18L ; DW18L ; W18L	516	1951	890	5851	925	TL	E4-106R-001829

Printed on 5/6/2024 10:33 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..