

AGRIMAX TURF RT 333 - Technical Specifications



Description

AGRIMAX TURF RT 333 (R-3+) is a radial tire designed for small tractors in gardening, vineyards and orchards applications. Its rounded shoulder design provides low soil compaction and makes it extremely delicate on the ground. Its unique extra-deep tread (R-3+) and the special design with directional blocks stand for excellent traction both in the field and on the road, and an extended tire life cycle. AGRIMAX TURF RT 333 (R-3+) ensures great self-cleaning properties and thanks to its low rolling resistance, allows for significant fuel saving.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Orchard Harvester • Small Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	240/60 R12
LI/SS	89 A8/B

Dimensions US Standard

Usa code	94070657
Section Width (inch)	9.5
Overall Diameter (inch)	23.3
Static Loaded Radius (inch)	10.6
Rolling Circumference (inch)	70
Rim Rec	W7
ECE	E11-106R-007679

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
30	600	690	790	880	990	1070	1200	1280
25	600	690	790	880	990	1070	1200	1280
20	640	740	850	940	1050	1150	1290	1380
5 LT	800	920	1060	1180	1320	1440	1610	1720
5 HT	640	740	850	940	1050	1150	1290	1380

Printed on 5/6/2024 10:06 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..