

# AGRIMAX TURF RT 333 - Technical Specifications



## Description

AGRIMAX TURF RT 333 (R-3+) is a radial tire designed for small tractors in gardening, vineyards and orchards applications. Its rounded shoulder design provides low soil compaction and makes it extremely delicate on the ground. Its unique extra-deep tread (R-3+) and the special design with directional blocks stand for excellent traction both in the field and on the road, and an extended tire life cycle. AGRIMAX TURF RT 333 (R-3+) ensures great self-cleaning properties and thanks to its low rolling resistance, allows for significant fuel saving.

## UM

US Standard

## Construction

 RADIAL

## Machinery

Agriculture: Orchard Harvester • Small Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	380/70 R 20
LI/SS	122 A8/122 B

## Dimensions US Standard

Usa code	94068821
Section Width (inch)	15
Overall Diameter (inch)	42.6
Static Loaded Radius (inch)	19.1
Rolling Circumference (inch)	126.5
Rim Rec	W 12
Rim Alt	W 11 ; W 13
ECE	E11-106R-007111

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	1820	2120	2420	2720	3010	3310
25	1820	2120	2420	2720	3010	3310
20	1960	2280	2600	2910	3230	3540
5 LT	2450	2850	3250	3640	4040	4440
5 HT	1960	2280	2600	2910	3230	3540

Printed on 5/7/2024 12:19 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..