

AGRIMAX TURF RT 333 - Technical Specifications



Description

AGRIMAX TURF RT 333 (R-3+) is a radial tire designed for small tractors in gardening, vineyards and orchards applications. Its rounded shoulder design provides low soil compaction and makes it extremely delicate on the ground. Its unique extra-deep tread (R-3+) and the special design with directional blocks stand for excellent traction both in the field and on the road, and an extended tire life cycle. AGRIMAX TURF RT 333 (R-3+) ensures great self-cleaning properties and thanks to its low rolling resistance, allows for significant fuel saving.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Orchard Harvester • Small Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	480/70 R 34
LI/SS	149 A8 / 149 B

Dimensions International Standard

Section Width (mm)	479
Overall Diameter (mm)	1580
Static Loaded Radius (mm)	723
Rolling Circumference (mm)	4785
SRI (mm)	750
Rim Rec	W 15 L
Rim Alt	W 14 L ; W 16 L
ECE	E11-106R-009042

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	1530	1755	2015	2275	2535	2795	3055	3250
40	1530	1755	2015	2275	2535	2795	3055	3250
30	1640	1880	2160	2440	2715	2995	3275	3480
10 LT	2050	2355	2705	3050	3400	3750	4095	4355
10 HT	1640	1880	2160	2440	2715	2995	3275	3480

Printed on 5/7/2024 2:10 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..