

# AGRIMAX V-FLECTO - Technical Specifications



## Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the exclusive VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

## UM

International Standard

## Construction

RADIAL

## Machinery

Agriculture: High-Power Tractor

Version	STANDARD
Type	TL
Tyre Size	VF 600/60 R 28 NRO
LI/SS	157 D

## Dimensions International Standard

Section Width (mm)	587
Overall Diameter (mm)	1440
Static Loaded Radius (mm)	632
Rolling Circumference (mm)	4228
SRI (mm)	675
Rim Rec	DW 20 B
Rim Alt	DW 18 L
Narrow Rim option	DW 18 L
ECE	E11-106R-004471
TRA Code	R1W

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
70	2060	2400	2735	3075	3410	3750
from 65 to 40	2265	2640	3010	3380	3750	4125
30	2310	2690	3070	3445	3825	4205
20	2355	2745	3130	3515	3900	4290
10	2490	2900	3310	3715	4125	4535
*Upto 10 Cyc with front loader	3170	3695	4210	4730	5250	5775
10HT	2310	2690	3070	3445	3825	4205

\* \*For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Printed on 5/6/2024 8:33 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..