

AGRIMAXFACTOR - Technical Specifications



Description

AGRIMAXFACTOR is BKT's brand-new 70 series for tractors that is perfect for both haulage and soil tillage operations. The improved tread design with further increased lug length and changed lug orientation stands for better roadability. The reduced lug angle ensures less rolling resistance, whilst the by 5 % increased contact area on the land significantly reduced the noise perception in the cabin – both features stand for more comfort. In addition, the strong polyester casing provides extraordinary lateral stability and a faster steering response even for high-speed operations or heavy-duty service. The tire's braking results on wet surface are excellent.

In a nutshell, AGRIMAXFACTOR's overall advantages are great handling in combination with under many aspects extraordinary driving comfort in addition to excellent durability – all particular requirements by increasingly heavier machinery including the higher weight of evehicles' battery packages. The exclusive sidewall shows the perfectly aligned "E-READY" logo that highlights BKT's commitment to electric mobility.

UM

International Standard

Construction



Machinery

Agriculture: Tractor

Version	STANDARD
Туре	TL
Tyre Size	580/70 R 42
LI/SS	158 D/161 A8

Dimensions International Standard

Section Width (mm)	577
Overall Diameter (mm)	1879
Static Loaded Radius (mm)	856
Rolling Circumference (mm)	5693
SRI (mm)	900
Rim Rec	W 18 L
Rim Alt	DW18L;DD18L
ECE	E11-106R-0010076
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1	1.2	1.4	1.6
65	2340	2720	3105	3485	3870	4250
50	2460	2860	3260	3665	4065	4465
40	2545	2960	3380	3795	4210	4625
30	2690	3130	3570	4010	4450	4890
10 LT	3135	3645	4160	4670	5185	5695
10HT	2690	3130	3570	4010	4450	4890

Printed on 5/6/2024 7:17 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..