

AGRIMAXFACTOR - Technical Specifications



Description

AGRIMAXFACTOR is BKT's brand-new 70 series for tractors that is perfect for both haulage and soil tillage operations. The improved tread design with further increased lug length and changed lug orientation stands for better roadability. The reduced lug angle ensures less rolling resistance, whilst the by 5 % increased contact area on the land significantly reduced the noise perception in the cabin – both features stand for more comfort. In addition, the strong polyester casing provides extraordinary lateral stability and a faster steering response even for high-speed operations or heavy-duty service. The tire's braking results on wet surface are excellent.

In a nutshell, AGRIMAXFACTOR's overall advantages are great handling in combination with under many aspects extraordinary driving comfort in addition to excellent durability – all particular requirements by increasingly heavier machinery including the higher weight of e-vehicles' battery packages. The exclusive sidewall shows the perfectly aligned "E-READY" logo that highlights BKT's commitment to electric mobility.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	620/70 R 42
LI/SS	160 D/163 A8

Dimensions US Standard

Usa code	94073610
Section Width (inch)	24.6
Overall Diameter (inch)	76.2
Static Loaded Radius (inch)	34
Rolling Circumference (inch)	227.8
Rim Rec	DW 20 B
Rim Alt	DW18L ; W18L
ECE	E11-106R-007764
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
40	5460	6350	7240	8130	9030	9920
30	5730	6670	7610	8540	9480	10420
25	5990	6970	7940	8920	9900	10870
20	6280	7310	8330	9360	10380	11410
5 LT	7320	8510	9710	10900	12100	13290
5 HT	6280	7310	8330	9360	10380	11410

Printed on 5/6/2024 5:15 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..