

# AGRIMAXFACTOR - Technical Specifications



## Description

AGRIMAXFACTOR is BKT's brand-new 70 series for tractors that is perfect for both haulage and soil tillage operations. The improved tread design with further increased lug length and changed lug orientation stands for better roadability. The reduced lug angle ensures less rolling resistance, whilst the by 5 % increased contact area on the land significantly reduced the noise perception in the cabin – both features stand for more comfort. In addition, the strong polyester casing provides extraordinary lateral stability and a faster steering response even for high-speed operations or heavy-duty service. The tire's braking results on wet surface are excellent.

In a nutshell, AGRIMAXFACTOR's overall advantages are great handling in combination with under many aspects extraordinary driving comfort in addition to excellent durability – all particular requirements by increasingly heavier machinery including the higher weight of e-vehicles' battery packages. The exclusive sidewall shows the perfectly aligned "E-READY" logo that highlights BKT's commitment to electric mobility.

## UM

US Standard

## Construction

 RADIAL

## Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	710/70 R 38
LI/SS	171 D/174 A8

## Dimensions US Standard

Usa code	94071159
Section Width (inch)	28.2
Overall Diameter (inch)	77.1
Static Loaded Radius (inch)	34.1
Rolling Circumference (inch)	228.3
Rim Rec	DW 23 B
Rim Alt	DW 25 B
ECE	E11-106R-007637
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
40	6380	7330	8410	9490	10580	11660	12750	13560
30	6700	7690	8840	9980	11110	12260	13390	14240
25	6940	7980	9160	10340	11530	12710	13890	14770
20	7340	8430	9680	10920	12170	13410	14670	15600
5 LT	8550	9820	11280	12730	14190	15640	17100	18180
5 HT	7340	8430	9680	10920	12170	13410	14670	15600

Printed on 5/6/2024 10:11 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..