

FL 630 ULTRA - Data Sheet

Description

FL 630 ULTRA is suitable for trailers, tankers and spreaders. Thanks to its reinforced bead and the particular tread design, it is the ideal tire for multipurpose use on any kind of land or on the road. FL 630 ULTRA stands for extraordinarily reduced soil compaction.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Spreader • Tanker • Trailer



SIZE	Version	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
500/60 R 22.5	STANDARD	155 D/166 A8	AG 16.00	15.00 ; 16.00 ; 17.00	503	1172	521	3592	550	TL	E4-106R-001404
560/45 R 22.5	STANDARD	152 D/163 A8	AG 16.00		543	1076	490	3290	525	TL	E11-106R-003012
560/60 R 22.5	STANDARD	161 D/172 A8	AG 16.00	16.00 ; 17.00 ; AG 20.00	543	1244	535	3760	600	TL	E11-106R-003013
600/50 R 22.5	STANDARD	159 D/170 A8	AG 20.00		611	1172	518	3533	550	TL	E11-106R-003960
710/40 R 22.5	STANDARD	161 D/172 A8	AG 24.00		727	1140	514	3490	550	TL	E11-106R-003016
600/55 R 26.5	STANDARD	165 D/176 A8	AG 20.00		611	1333	579	4070	625	TL	E11-106R-006813
650/55 R 26.5	STANDARD	169 D/180 A8	AG 20.00		645	1389	600	4207	650	TL	E11-106R-006814
710/50 R 26.5	STANDARD	170 D/181 A8	AG 24.00	AG 20.00	727	1383	599	4208	650	TL	E11-106R-006812
800/45 R 26.5	STANDARD	174 D/184 A8	AG 28.00	AG 24.00	828	1393	618	4238	675	TL	E11-106R-004074

Printed on 5/6/2024 6:56 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..