



RIDEMAX FL 690 - Data Sheet

Description

RIDEMAX FL 690 is a radial flotation and transport tire for tank trucks and trailers. The tire is suitable for 75% on-the-road applications. As a response to the increasing demand for high loads in modern agriculture, BKT has designed this steel-belted tire withstanding very heavy loads and increasing the farmer's productivity. The low rolling resistance contributes to better fuel economy.



UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tanker • Trailer

Industrial: Trailer

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
28L R 26 (750/65 R 26)	STANDARD	94034321	176 A8/173 B	DW 25 B	DW 23 B	28.3	62.6	27.4	186.8	TL	E11-106R-002985
30.5L R 32	STANDARD	94033836	184 A8/181 B	DH 27 B	DW 27 B	31.1	70.9	31.7	213.8	TL	E11-106R-002986
800/60 R 32	STANDARD	94066254	185D	DH 27 B	DW 27 B	31.5	70.9	32.2	214.7	TL	E11-106R-006480
VF 900/65 R 32 (VF35.5LR32)	STANDARD	94067176	197 D	DW 31 B	DW 30 ; TW 30	36.6	78.2	33	231.4	TL	E11-106R-006917

Printed on 5/19/2024 3:16 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..