

RIDEMAX FL 693 M - Technical Specifications



Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption, while a reinforced bead and steel belts ensure enhanced durability.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tanker • Trailer

Version	STANDARD
Type	TL
Tyre Size	400/45 R 17.5
LI/SS	139 D

Dimensions US Standard

Usa code	94066063
Section Width (inch)	15.7
Overall Diameter (inch)	31.5
Static Loaded Radius (inch)	13.5
Rolling Circumference (inch)	92.8
Rim Rec	14.00
ECE	E11-106R-006619

Load capacity (lbs)

mph / psi	15	17	23	29	35	41	46	52	58	73	87
45	1220	1570	1960	2200	2550	2890	3170	3470	3810	4300	4880
40	1340	1720	2150	2410	2790	3160	3480	3810	4190	4720	5360
30	1630	2080	2600	2930	3380	3840	4220	4620	5070	5720	6490
25	1830	2340	2920	3280	3790	4300	4740	5180	5690	6420	7290
20	2030	2590	3240	3650	4210	4780	5270	5750	6320	7120	8090
15	2120	2710	3390	3810	4410	5000	5510	6020	6610	7450	8470
5	2410	3090	3860	4340	5020	5700	6270	6860	7530	8490	9640

Printed on 5/6/2024 10:17 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..