

RIDEMAX FL 693 M - Technical Specifications



Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption, while a reinforced bead and steel belts ensure enhanced durability.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tanker • Trailer

Version	STANDARD
Type	TL
Tyre Size	560/55 R 22.5
LI/SS	158 D/155 E

Dimensions US Standard

Usa code	94037353
Section Width (inch)	21.4
Overall Diameter (inch)	46.5
Static Loaded Radius (inch)	21
Rolling Circumference (inch)	142.3
Rim Rec	AG 16.00
Rim Alt	17.00 ; 20.00
ECE	E4-106R-000631

Load capacity (lbs)

mph / psi	15	17	23	29	35	41	46	52	58
45	3160	3590	4280	5050	5780	6420	7180	7860	8540
40	3470	3940	4680	5530	6330	7030	7870	8620	9370
30	4210	4770	5680	6700	7660	8510	9530	10440	11340
25	4720	5360	6370	7530	8610	9560	10710	11730	12740
15	5490	6230	7410	8740	10000	11110	12440	13620	14800
5	6250	7090	8430	9950	11390	12650	14170	15520	16860

Printed on 5/6/2024 7:25 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..