

RIDEMAX FL 693 M - Technical Specifications



Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks.

Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption, while a reinforced bead and steel belts ensure enhanced durability.

UM

International Standard

Construction



Machinery

Agriculture: Tanker • Trailer

Version	STANDARD
Туре	TL
Tyre Size	650/50 R 22.5
LI/SS	163 D/160 E

Dimensions International Standard

Section Width (mm)	645
Overall Diameter (mm)	1222
Static Loaded Radius (mm)	535
Rolling Circumference (mm)	3715
SRI (mm)	575
Rim Rec	AG 20.00
ECE	E4-106R-001417

Load capacity (Kg)

km/h / bar	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1645	1845	2295	2610	3015	3420	3735	4095	4500
65	1780	2000	2490	2830	3270	3705	4050	4440	4875
50	2155	2420	3010	3425	3955	4485	4900	5370	5900
40	2425	2720	3385	3850	4445	5040	5505	6035	6630
25	2815	3160	3930	4470	5165	5860	6400	7015	7705
10	3205	3600	4480	5090	5880	6670	7285	7990	8775

Printed on 5/6/2024 9:33 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..