



TR 463 - Data Sheet

Description

TR 463 has been specially designed for backhoe loaders and industrial tractors. Made of a superior tread compound and featuring a strong nylon casing, this tire stands for best results in industrial and OTR applications, and on construction sites. TR 463 provides excellent traction for drive wheels.



UM

US Standard

Construction

 BIAS

Machinery

Industrial: Backhoe Loader • Industrial Tractor

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
16.9 - 24	INDUSTRIAL	94053322	R4	149 A8	12	DW 15 L	DW 14 L	17.5	51.2	23	152.6	TL	
18.4 - 26	INDUSTRIAL	94057221	R4	156 A8	12	DW 16 L	DW 15 L	18.9	56.1	25.1	165.9	TL	
16.9 - 28	INDUSTRIAL	94053339	R4	152 A8	12	DW 15 L	DW 14 L	17.7	55.3	25	165	TL	E11-106R-003626

Printed on 5/6/2024 10:02 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..