

AGRIMAX V-FLECTO - Technical Specifications



Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the exclusive VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: High-Power Tractor

Version	STANDARD
Type	TL
Tyre Size	VF 710/60 R 42 NRO
LI/SS	173 D

Dimensions International Standard

Section Width (mm)	710
Overall Diameter (mm)	1930
Static Loaded Radius (mm)	860
Rolling Circumference (mm)	5786
SRI (mm)	925
Rim Rec	DW 25 B
Rim Alt	DW 23 B ; MW 25 B
Narrow Rim option	DW 23 B
ECE	E11-106R-002998
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
70	3250	3785	4315	4850	5380	5915
from 65 to 40	3575	4160	4745	5330	5915	6500
30	3645	4240	4835	5435	6030	6630
20	3715	4325	4930	5540	6150	6760
10	3930	4575	5215	5860	6505	7150
*Upto 10 Cyc with front loader	5005	5820	6640	7460	8280	9100
10HT	3645	4240	4835	5435	6030	6630

* *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Printed on 5/21/2024 5:09 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..