

AGRIMAX V-FLECTO - Technical Specifications



Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the exclusive VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: High-Power Tractor

Version	STANDARD
Type	TL
Tyre Size	VF 900/60 R 38 NRO
LI/SS	187 D

Dimensions US Standard

Usa code	94075096
Section Width (inch)	34.7
Overall Diameter (inch)	80.5
Static Loaded Radius (inch)	34.7
Rolling Circumference (inch)	238.3
Rim Rec	DW 30 B
Narrow Rim option	DW 27 B
ECE	E11-106R-009004
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29
45	9580	11140	12910	14470	16040	17600	19550
From 40 to 25	10530	12250	14190	15910	17620	19340	21490
20	10740	12490	14460	16210	17970	19730	21920
12	10950	12730	14750	16530	18320	20120	22350
5	11570	13470	15600	17490	19380	21270	23640
*Upto 5 Cyc with front loader	14740	17140	19850	22270	24670	27080	30090
5 HT	10740	12490	14460	16210	17970	19730	21920

* *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Printed on 5/20/2024 9:50 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..