

# AGRIMAXFACTOR - Technical Specifications



## Description

AGRIMAXFACTOR is BKT's brand-new 70 series for tractors that is perfect for both haulage and soil tillage operations. The improved tread design with further increased lug length and changed lug orientation stands for better roadability. The reduced lug angle ensures less rolling resistance, whilst the by 5 % increased contact area on the land significantly reduced the noise perception in the cabin – both features stand for more comfort. In addition, the strong polyester casing provides extraordinary lateral stability and a faster steering response even for high-speed operations or heavy-duty service. The tire's braking results on wet surface are excellent.

In a nutshell, AGRIMAXFACTOR's overall advantages are great handling in combination with under many aspects extraordinary driving comfort in addition to excellent durability – all particular requirements by increasingly heavier machinery including the higher weight of e-vehicles' battery packages. The exclusive sidewall shows the perfectly aligned "E-READY" logo that highlights BKT's commitment to electric mobility.

## UM

International Standard

## Construction

 RADIAL

## Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	480/70 R 38
LI/SS	145 D/148 A8

## Dimensions International Standard

Section Width (mm)	479
Overall Diameter (mm)	1681
Static Loaded Radius (mm)	758
Rolling Circumference (mm)	5000
SRI (mm)	800
Rim Rec	W 15 L
Rim Alt	W 14 L ; W 16 L
ECE	E11-106R-007654
TRA Code	R1W

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
65	1595	1860	2120	2380	2640	2900
50	1675	1950	2225	2500	2775	3045
40	1750	2040	2325	2610	2895	3180
30	1835	2135	2435	2735	3035	3335
10 LT	2140	2490	2840	3190	3540	3890
10 HT	1935	2135	2435	2735	3035	3335

Printed on 5/21/2024 3:16 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..