

## EARTHMAX SR 41 - Technical Specifications



### Description

EARTHMAX SR 41 is an All Steel radial tire perfect for Articulated Dump Trucks, Loaders and Dozers. Thanks to its all steel structure and special block pattern, EARTHMAX SR 41 provides excellent resistance against punctures and an extended service life. In addition to long working hours without downtime, the tire ensures extraordinary comfort. EARTHMAX SR 41 is also available in E4\*\*\*\* for Low Profile Dump Trucks (LPDT) used in underground haulage operations.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Articulated Dump Truck (ADT) • Dozer • Loader •  
Low Profile Dump Truck (LPDT)

Version	CUT RESISTANT COMPOUND (UMS)
Type	TL
Tyre Size	35/65 R 33

## Dimensions US Standard

Usa code	94069415
Overall Width (inch)	35.3
Overall Diameter (inch)	81.2
Static Loaded Radius (inch)	36.5
Rolling Circumference (inch)	247.4
Rim Rec	28.00/3.5
Rim Alt	--
Star Rating	****
TRA Code	E4

## Load capacity (lbs)

mph / psi

\* In case of underground mine application, consult your servicing dealer or BKT representative.

Printed on 5/21/2024 1:18 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..