

# RIDEMAX FL 693 M - Technical Specifications



## Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption, while a reinforced bead and steel belts ensure enhanced durability.

## UM

International Standard

## Construction

 RADIAL

## Machinery

Agriculture: Tanker • Trailer

Version	STANDARD
Type	TL
Tyre Size	400/45 R 17.5
LI/SS	139 D

## Dimensions International Standard

Section Width (mm)	400
Overall Diameter (mm)	800
Static Loaded Radius (mm)	343
Rolling Circumference (mm)	2357
SRI (mm)	390
Rim Rec	14.00
ECE	E11-106R-006619

## Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0	6.0
70	555	710	890	1000	1155	1310	1440	1575	1730	1950	2215
65	610	780	975	1095	1265	1435	1580	1730	1900	2140	2430
50	740	945	1180	1330	1535	1740	1915	2095	2300	2595	2945
40	830	1060	1325	1490	1720	1950	2150	2350	2580	2910	3305
30	920	1175	1470	1655	1910	2170	2390	2610	2865	3230	3670
25	960	1230	1540	1730	2000	2270	2500	2730	3000	3380	3840
10	1095	1400	1750	1970	2275	2585	2845	3110	3415	3850	4375

Printed on 5/21/2024 2:42 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..