

## RIDEMAX IT 697 (M+S) - Technical Specifications



### Description

RIDEMAX IT 697 M+S represents the best response to the needs of modern farming contractors during winter operations. It is perfect for haulage and municipality applications. This winter tire for tractors ensures extraordinary grip for all operations on icy and snowy roads without the need of snow chains being mounted. Thanks to the tread grooves and the strong casing, a tractor can be driven in full stability, also at high speed levels. The tread design has been specially developed for heavy-duty services and ensures a low rolling resistance that provides fuel economy plus great stability.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	650/65 R 38 IND
LI/SS	170 D/175 A8

## Dimensions US Standard

Usa code	94055418
TMPH	1
Section Width (inch)	25.4
Overall Diameter (inch)	71.3
Static Loaded Radius (inch)	32.4
Rolling Circumference (inch)	217.1
Rim Rec	DW 20 B
Rim Alt	DW 18 L
ECE	E11-106R-004078

## Load capacity (lbs)

mph / psi	17	23	29	35	41	46
40	6220	7670	8990	10450	11770	13230
30	6710	8290	9710	11290	12710	14290
25	7150	8820	10340	12010	13540	15210
20	7460	9200	10790	12540	14130	15870

Printed on 5/21/2024 12:51 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..