

AGRIMAX RT 600 - Technische Daten

Description

AGRIMAX RT 600 ist der ideale Reifen für Grasflächen sowie Ernte- und Spritzanwendungen. Mit seiner breiten Aufstandsfläche bietet AGRIMAX RT 600 eine optimale Druckverteilung auf dem Boden, reduziert den Schaden von Grasland und schützt den Boden. Dank der abgerundeten Schulterstruktur, dem verstärkten Wulst und der größeren Stollenzahl gewährleistet er ausgezeichnete Stabilität und Traktion.

UM

International Standard

Construction

 RADIAL

Machinery

Landwirtschaft: Erntemaschine • Streumaschine • Traktor



Version	STANDARD
Type	TL
Tyre Size	800/65 R 32 (30.5L R 32)
LI/SS	176 A8/173 B

Dimensions International Standard

Section Width (mm)	775
Overall Diameter (mm)	1820
Static Loaded Radius (mm)	823
Rolling Circumference (mm)	5558
SRI (mm)	875
Rim Rec	DW 27 B
Rim Alt	DH 27 B ; DW 25 B
ECE	E4-106R-001428

Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.0	3.2	3.6
50	3175	3660	4485	4900	5385	5865	6350	6500	-	-
40	3450	3975	4875	5325	5850	6375	6900	7100	-	-
30	3695	4255	5220	5700	6260	6825	7385	7600	-	-
10 LT	4625	5330	6535	7140	7840	8545	9250	9515	-	-
10 HT	3695	4255	5220	5700	6260	6825	7385	7600	-	-
10 Cyc.	-	5655	7230	7960	9250	10140	11055	11540	12025	12440

Printed on 20.05.2024 18:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..