

AGRIMAX RT 765M - Technische Daten



Description

AGRIMAX RT 765M, ein Reifen der BKT 70er Serie, ist für den Einsatz mit hochmodernen Traktoren auf dem neuesten Stand der Technik in verschiedenen Schwerlastanwendungen wie Bodenbearbeitung, Feld- und Straßenfahrten, Weinlese sowie Sprüheinsätze geeignet. Eine breite Aufstandsfläche gewährleistet jederzeit bestmögliche Traktion auf allen Bodenflächen. Der Reifen bietet großartige Selbstreinigungseigenschaften sowie reduzierte Bodenverdichtung. Zwei Größen sind mit Stahlbandtechnologie erhältlich.

UM

US Standard

Construction

 RADIAL

Machinery

Landwirtschaft: Feldspritze • Traktor • Traubenerntemaschine

Version	STANDARD
Type	TL
Tyre Size	710/70 R 42
LI/SS	173D/176A8

Dimensions US Standard

Usa code	94066452
Section Width (inch)	28.2
Overall Diameter (inch)	81.1
Static Loaded Radius (inch)	36.3
Rolling Circumference (inch)	243.1
Rim Rec	DW 23 B
Rim Alt	DW 25 B
ECE	E11-106R-006018
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
40	6730	7740	8880	10030	11180	12320	13470	14330
30	7080	8130	9340	10540	11740	12940	14150	15050
25	7390	8480	9730	10990	12250	13500	14760	15700
15	7750	8910	10220	11540	12860	14170	15500	16480
5 LT	9030	10370	11920	13450	14980	16520	18050	19200
5 HT	7750	8910	10220	11540	12860	14170	15500	16480

Printed on 20.05.2024 23:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..