

## AT 625 - Technische Daten



### Description

AT 625 eignet sich für Baggerlader und Kompaktlader bei allen Bagger- und Ladearbeiten in der Landwirtschaft. Die extra tiefe Lauffläche steht für verstärkte Durchstichfestigkeit und Beständigkeit. AT 625 zeichnet sich durch ausgezeichnete Traktion und Stabilität sowie verbesserte Schnitt- und Reißfestigkeit aus.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrie: Baggerlader • Kompaktlader

Version	SPECIAL
Type	TT
Tyre Size	16.9 - 28
LI/SS	152 A8

## Dimensions International Standard

Ply Rating	12
Section Width (mm)	450
Overall Diameter (mm)	1415
Static Loaded Radius (mm)	645
Rolling Circumference (mm)	4254
Rim Rec	DW 15 L
Rim Alt	DW 14 L
TRA Code	R4

## Load capacity (Kg)

km/h / bar	2.60
40	3550

Printed on 20.05.2024 23:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..