

FL 630 ULTRA - Technische Daten



Description

FL 630 ULTRA ist besonders für den Einsatz mit Anhängern, Tankwagen und Streumaschinen geeignet. Dank des verstärkten Wulstes und dem speziellen Laufflächendesign ist der Reifen ideal zum Mehrzweck Einsatz auf jeder Art von Boden oder auf der Straße. FL 630 ULTRA steht für außerordentlich reduzierte Bodenverdichtung.

UM

International Standard

Construction

 RADIAL

Machinery

Landwirtschaft: Streumaschine • Tankwagen • Anhänger

Version	STANDARD
Type	TL
Tyre Size	710/50 R 26.5
LI/SS	170 D/181 A8

Dimensions International Standard

Section Width (mm)	727
Overall Diameter (mm)	1383
Static Loaded Radius (mm)	599
Rolling Circumference (mm)	4208
SRI (mm)	650
Rim Rec	AG 24.00
Rim Alt	AG 20.00
ECE	E11-106R-006812

Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1750	1995	2240	2785	3170	3660	4150	4535	4970	5460
65	1920	2190	2460	3060	3480	4020	4560	4980	5460	6000
50	2325	2650	2980	3705	4210	4865	5520	6025	6610	7260
40	2640	3015	3385	4210	4785	5530	6270	6850	7510	8250
25	3035	3465	3890	4835	5500	6355	7205	7870	8630	9480
10	3460	3945	4430	5510	6265	7240	8210	8965	9830	10800

Printed on 21.05.2024 12:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..