

MULTIMAX MP 522 - Technische Daten



Description

MULTIMAX MP 522 ist BKTs Mehrzweckreifen für agro-industrielle Anwendungen. Er eignet sich für alle Bagger- und Ladearbeiten mit Fahrzeugen wie Teleskopladern und Kompaktladern. Stabilität und hohe Traktion sind seine Stärken neben erstklassiger Durchstichfestigkeit. Dank der speziellen Gummimischung ist MULTIMAX MP 522 außergewöhnlich widerstandsfähig gegenüber Schnitten und Rissen.

UM

International Standard

Construction

 RADIAL

Machinery

Landwirtschaft: Kompaktlader • Teleskoplader
Industrie: Kompaktlader • Teleskoplader

Version	STANDARD
Type	TL
Tyre Size	480/80 R 26 IND
LI/SS	160 A8/B

Dimensions International Standard

Section Width (mm)	479
Overall Diameter (mm)	1428
Static Loaded Radius (mm)	638
Rolling Circumference (mm)	4287
SRI (mm)	675
Rim Rec	DW 15 L
Rim Alt	DW 16 L
ECE	E11-106R-002970

Load capacity (Kg)

km/h / bar	1.6	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6
50	2610	3060	3330	3555	3780	4005	4275	4500	-	-
40	2610	3060	3330	3555	3780	4005	4275	4500	-	-
30	2795	3275	3565	3805	4045	4290	4575	4815	-	-
25	2900	3400	3700	3950	4200	4450	4750	4995	-	-
10 Cyc.	3175	3915	4255	4590	4995	5335	5670	6075	6415	6750
Static	4865	6005	6525	7040	7660	8180	8695	9315	9835	10350

Printed on 21.05.2024 19:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..