

## AGRIMAX TURF RT 333 - Especificaciones técnicas



### Description

El AGRIMAX TURF RT 333 (R-3+) es un neumático radial diseñado para pequeños tractores utilizados para aplicaciones de jardinería, viñedos y huertos. Su diseño de hombro redondeado ofrece una baja compactación del suelo y lo hace extremadamente delicado sobre el terreno. Su exclusiva banda de rodadura extraprofunda (R-3+) y el diseño especial con bloques direccionales ofrecen una excelente tracción tanto en el campo como en carretera, así como una mayor duración del ciclo de vida útil del neumático. El AGRIMAX TURF RT 333 (R-3+) garantiza unas magníficas propiedades de autolimpieza y, gracias a su reducida resistencia a la rodadura, permite un significativo ahorro de combustible.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricultura: Maquina para la recogida de fruta •  
Minitractor • Vendimiadora

Version	STANDARD
Type	TL
Tyre Size	280/70 R 18
LI/SS	114 A8/114 B

## Dimensions International Standard

Section Width (mm)	289
Overall Diameter (mm)	840
Static Loaded Radius (mm)	390
Rolling Circumference (mm)	2550
SRI (mm)	410
Rim Rec	W 9
Rim Alt	W 8 ; W 10
ECE	E11-106R-006473

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	555	640	735	830	925	1015	1110	1180
40	555	640	735	830	925	1015	1110	1180
30	595	685	785	890	990	1090	1190	1265
10 LT	745	860	985	1110	1240	1365	1490	1585
10 HT	595	695	785	890	990	1090	1190	1265

Printed on 21/05/2024 2:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..