

AGRIMAX V-FLECTO - Especificaciones técnicas



Description

AGRIMAX V-FLECTO es la respuesta de BKT a la demanda desafiante en clave de la tecnología y las prestaciones de los tractores de elevada potencia. Este neumático es perfecto para aplicaciones de tratamiento del terreno y de transporte gracias a una menor compactación del suelo. Con la tecnología exclusiva VF, AGRIMAX V-FLECTO permite transportar cargas pesadas con una presión de inflado inferior en comparación con un neumático estándar o IF, alcanzando velocidades elevadas. Presenta l'Opción de Llanta Estrecha (NRO) que permite el montaje de llantas estándar. BKT ha diseñado este neumático con una geometría optimizada que incrementa el confort de conducción en el campo y por carretera reduciendo el consumo de carburante.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Tractor de alta potencia

Version	STANDARD
Type	TL
Tyre Size	VF 480/80 R 38
LI/SS	166 D

Dimensions US Standard

Usa code	94067220
Section Width (inch)	18.9
Overall Diameter (inch)	68.2
Static Loaded Radius (inch)	30.5
Rolling Circumference (inch)	203.5
Rim Rec	DW 16 L
Rim Alt	DW 15 L
ECE	E11-106R-007168
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
45	5000	5740	6590	7440	8290	9150	10000	10630
From 40 to 25	5500	6320	7250	8180	9120	10050	10990	11680
20	5610	6440	7400	8340	9300	10250	11210	11920
12	5710	6570	7540	8510	9480	10450	11420	12150
5	6050	6940	7970	9010	10030	11060	12090	12850
*Upto 5 Cyc with front loader	7690	8840	10150	11450	12760	14080	15380	16360
5 HT	5610	6440	7400	8340	9300	10250	11210	11920

* *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Printed on 21/05/2024 7:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..