

## AT 625 - Especificaciones técnicas



### Description

AT 625 es idóneo para instalarlo en las ternas y las palas compactas que se utilizan en todas las operaciones de excavación y carga en el ámbito agrícola. La banda de rodadura extra profunda garantiza una incrementada resistencia a la perforación y una mayor durabilidad. AT 625 ofrece una excelente tracción y estabilidad, así como una mejor resistencia a los cortes y los desgarros.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrial: Cargadora retroexcavadora • Cargadora compacta

Version	SPECIAL
Type	TT
Tyre Size	16.9 - 28
LI/SS	152 A8

## Dimensions US Standard

Usa code	94055470
Ply Rating	12
Section Width (inch)	17.7
Overall Diameter (inch)	55.7
Static Loaded Radius (inch)	25.4
Rolling Circumference (inch)	167.5
Rim Rec	DW 15 L
Rim Alt	DW 14 L
TRA Code	R4

## Load capacity (lbs)

mph / psi	38
25	7850

Printed on 21/05/2024 2:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..