

EARTHMAX SR 423 - Especificaciones técnicas



Description

EARTHMAX SR 423 es un neumático radial All Steel para una amplia serie de aplicaciones, incluidas las operaciones en las conteras y en el sector forestal y del transporte. El dibujo no direccional de la banda de rodadura asegura una óptima tracción y estabilidad en cualquier tipo de terreno. Este neumático es ideal para el transporte de cargas pesadas. La robusta carcasa All Steel se distingue por una excelente resistencia al desgaste y contra cortes y pinchazos. La banda de rodadura reforzada y el diseño del hombro contribuyen a un ciclo de vida más largo incluso en las condiciones de trabajo más pesadas.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Volquete

Version	STANDARD
Type	TT
Tyre Size	12.00 R 24 (325/95 R 24)
LI/SS	160/156 K

Dimensions International Standard

Ply Rating	20
Overall Width (mm)	318
Overall Diameter (mm)	1243
Rim Rec	8.50

Load capacity (Kg)

	km/h / bar	8.50
	110 Load Single	4500
	110 Load Dual	4000

Printed on 21/05/2024 5:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..