

EARTHMAX SR 55 - Ficha técnica



Description

EARTHMAX SR 55 (L-55) es un neumático radial All Steel especialmente proyectado para las palas cargadoras, los buldóceres y las cargadoras que operan en condiciones muy difíciles, como en las canteras, las minas y en los depósitos de chatarra. Gracias al dibujo de la banda de rodadura extra profundo y liso, EARTHMAX SR 55 puede alcanzar elevados niveles de productividad con menores tiempos de parada de la máquina. Los operadores de las máquinas apreciarán también estabilidad y tracción extraordinarias.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Buldócer • Cargadora LHD • Pala cargadora

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
12.00 R 24	CUT RESISTANT COMPOUND	L5S	**	175 A2	8.50/1.3	8.0,9.0	305	1274	572	3787	TT
12.00 R 24	CUT RESISTANT COMPOUND	L5S	**	175 A2	8.50/1.3	8.0,9.0	305	1274	572	3787	TL
17.5 R 25	CUT RESISTANT COMPOUND	L5S	**	182 A2	14.00/1.5		453	1399	630	4211	TL
17.5 R 25	CUT RESISTANT COMPOUND	L5S	***	188 A2	14.00/1.5		453	1399	630	4211	TL
18.00 R 25	CUT RESISTANT COMPOUND	L5S	**	204 A2	13.00/2.5		513	1667	733	4852	TL
20.5 R 25	CUT RESISTANT COMPOUND	L5S	**	193 A2	17.00/2.0		535	1543	700	4644	TL
26.5 R 25	CUT RESISTANT COMPOUND	L5S	**	209 A2	22.00/3.0		690	1786	810	5375	TL
26.5 R 25	CUT RESISTANT COMPOUND	L5S	***	214 A2	22.00/3.0		690	1786	810	5375	TL
29.5 R 25	CUT RESISTANT COMPOUND	L5S	**	216 A2	25.00/3.5		777	1912	860	5755	TL
29.5 R 29	CUT RESISTANT COMPOUND	L5S	**	218 A2	25.00/3.5	24.00/3.5, 26.00/3.5	775	2009	911	6047	TL
35/65 R 33	CUT RESISTANT COMPOUND	L5S	***	229 A2	28.00/3.5	--	900	2065	915	6175	TL
35/65 R 33	CUT RESISTANT COMPOUND	L5S	**	224 A2	28.00/3.5	--	900	2065	915	6175	TL

Printed on 21/05/2024 1:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..