

## RIDEMAX FL 693 M - Especificaciones técnicas



### Description

RIDEMAX FL 693 M es el neumático ideal para quien tiene que desplazarse frecuentemente por la carretera con remolques/auto cisternas. Desarrollado para utilizarlo en un 75% por carretera, RIDEMAX FL 693 M ofrece excelentes prestaciones por carretera, dando la prioridad al confort y a las propiedades de auto-limpieza. El índice de velocidad clase D/E de la gama es sinónimo de velocidades más elevadas por carretera, con un significativo ahorro de tiempo. La baja resistencia al rodamiento contribuye a un consumo menor de carburante, mientras que la banda de rodadura reforzada y los cinturones de acero aseguran mayor durabilidad.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Camión cisterna • Remolque

Version	STANDARD
Type	TL
Tyre Size	425/55 R17
LI/SS	129 D/140 A8

## Dimensions US Standard

Usa code	94059324
Section Width (inch)	16.5
Overall Diameter (inch)	35.2
Static Loaded Radius (inch)	15.6
Rolling Circumference (inch)	106.5
Rim Rec	13.00
ECE	E11-106R-005104

## Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58
40	1310	1680	2080	2370	2730	3110	3390	3710	4080
30	1590	2030	2520	2870	3320	3760	4100	4500	4940
25	1760	2260	2810	3200	3690	4190	4570	5020	5510
20	1970	2540	3150	3580	4130	4680	5110	5610	6160
15	2070	2650	3300	3750	4320	4910	5360	5870	6450
5	2360	3020	3750	4270	4930	5590	6100	6690	7340

Printed on 21/05/2024 3:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..