

RIDEMAX FL 693 M - Especificaciones técnicas



Description

RIDEMAX FL 693 M es el neumático ideal para quien tiene que desplazarse frecuentemente por la carretera con remolques/auto cisternas. Desarrollado para utilizarlo en un 75% por carretera, RIDEMAX FL 693 M ofrece excelentes prestaciones por carretera, dando la prioridad al confort y a las propiedades de auto-limpieza. El índice de velocidad clase D/E de la gama es sinónimo de velocidades más elevadas por carretera, con un significativo ahorro de tiempo. La baja resistencia al rodamiento contribuye a un consumo menor de carburante, mientras que la banda de rodadura reforzada y los cinturones de acero aseguran mayor durabilidad.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Camión cisterna • Remolque

Version	STANDARD
Type	TL
Tyre Size	500/45 R 22.5
LI/SS	146 D/143 E

Dimensions US Standard

Usa code	94043767
Section Width (inch)	19.8
Overall Diameter (inch)	40.2
Static Loaded Radius (inch)	17.9
Rolling Circumference (inch)	122.6
Rim Rec	AG 16.00
ECE	E4-106R-000786

Load capacity (lbs)

mph / psi	15	17	23	29	35	41	46	52	58
45	2200	2470	3060	3490	4030	4570	4990	5470	6010
40	2410	2710	3370	3840	4430	5030	5490	6020	6610
30	2930	3280	4090	4650	5370	6080	6650	7290	8000
25	3300	3690	4600	5220	6030	6840	7470	8190	8990
15	3820	4290	5330	6060	7010	7950	8670	9510	10450
5	4350	4880	6070	6910	7980	9050	9890	10840	11900

Printed on 20/05/2024 22:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..